

SZ-200-36M-A

Warranty

- ◆ 5 year Manufacturer Warranty
- ◆ Warranty on Electrical Performance:
5 years 80% of power output.

Manufacturing

- ◆ Original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing.
- ◆ Comprehensive module power testing.

Performance

- ◆ Upgraded module efficiency and portability.
- ◆ Weakened hot-spot effect, lower module failure rate and increased stability by shingle-tech.
- ◆ Optimized performance under low light conditions.
- ◆ Unique cell connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ◆ MC4 outputs.

Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	200W
Cell Type	Monocrystalline
Cell Efficiency	22.0%
Maximum Power Current (Impp)	11.02A
Maximum Power Voltage (Vmpp)	18.15V
Open-circuit Voltage (Voc)	21.57V
Short-circuit Current (Isc)	11.69A
Surface Material	Glass
Output Tolerance	±3%
Output	MC4
DC Output Current	/
Output USB-A	/
Output USB-QC	/
Certification	CE, RoHS
Working Temperature	-40°C~+80°C

Packaging

Folded Dimensions	595*565*50(mm)
Expanded Dimensions	2070*595*30(mm)
Module Weight	10kg
Pieces per Pallet	Free
Gross Weight per Pallet	Free
Pallet Dimensions	Free



FRONT



UNFOLDED



JUNCTION BOX

SOLMAX NEW ENERGY B.V.

Address: Defensiedok 18, 3433 KL, Nieuwegein, NL

Email: info15@solarfam.nl

